



PACK MULE

RELIABLE PRODUCTS AND SERVICE



BC-500



BC-500 STANDARD FEATURES

Industry Leading 3 Year Warranty

Dual Front Wheels

Programmable Performance Characteristics
(Maximum Speed, Acceleration Rate, etc.)

Heavy Duty 245 Amp/Hour Batteries

Premium On-Board High Frequency Charger
with temperature compensation & automatic
cell equalization to extend the life of the
batteries

Precision Track, Direct Gear Steering

Sealed Direct Drive Transaxle

Heavy Duty Horn

6 Ply Load Range C Tires

Electronic Throttle

Maintenance Management System

Dashboard Smart Gauge (L.E.D. Battery
Status, Hour Meter & Diagnostic Codes)

State-of-the Art, Fully Sealed, Tamper Proof
& Programmable Controller with On-Board
Diagnostics

Programmable Regenerative Braking

Extra Heavy-Duty Steel Construction (10
Gauge Uni-Body Internal Frame & 14 Gauge
Genuine Diamond Plate Exterior)

Electronic Throttle

Contactor-less Drive System

Universal Hitch Plate

BC-500

STOCK CHASER - BURDEN CARRIER - TOW TRACTOR - MAINTENANCE VEHICLE - PERSONNEL CARRIER

OPTIONAL EQUIPMENT
Upgrade to Maintenance Free AGM 250 Amp/Hour Batteries
AC Drive System
Roll Out Battery Exchange System
Carts with Chargers for Roll Out Batteries
Solid Rubber Tires
Solid Non-Marking Rubber Tires
Cushion Solid Rubber Tires
Left Foot Operator's Presence Switch
Back-Up Alarm
Proximity Alarm
Flashing Safety Beacon
Head Light, Tail Light, Brake Light
Hand Lever Parking Brake
Galvanized & Stainless Steel Decks
Galvanized Frame
Protective Front Guard with Rubber Bumpers
Extended Deck Lengths
Deck Shelves
Stake Bed
Custom Cargo Restraints
Modular Work Station
Mounted Clipboards (Large & Small)
Variety of Hitches
Perma-Key Switch
Programmable Key Switch
12 Volt Power Supply for Electronic Devices
Diagnostic Handset

DIMENSIONS	
Length	78 in. (198.1 cm)
Width	29 in. (73.7 cm)
Height	44 in. (111.8 cm)
Wheel Base	67 in (170.2 cm)
Ground Clearance	3 in. (7.6 cm)
Deck Height	22.5 in. (57.2 cm)
Deck	Rear: 28.5 in. (72.4 cm) x 30 in. (76.2 cm)
	Front: 28.5 in. (72.4 cm) x 18 in. (45.7 cm)
Turning Radius	74.5 in. (189.2 cm)
CAPACITIES	
Maximum Personnel	1
Deck	1000 lbs. (453.6 kg)
Towing	2000 lbs. (907.2 kg)
WHEELS & TIRES	
Wheels	4
Tires	Pneumatic 4.80 x 8 LRC (6 Ply)
ELECTRICAL	
Batteries	245 Amp-Hr Lead Acid, Commercial
System Voltage (Battery Quantity)	24 v. (4-6 v.)
Sealed Motor (Separately Excited)	5 hp (24 v.)
Sealed Programmable Controller	300 Amp (24v)
On-Board High Frequency Charger	25 Amp (24 v.)
Key Switch	Removable Safety Key Switch
Horn	Push Button on Console
STEERING, BRAKES, TRANSAXLE & SUSPENSION	
Steering	3-Spoke Contour Wheel
Service Brakes	Self- Adjusting Wheel Drum Brakes
Electronic Brakes	Programmable Electronic Regenerative Braking
Parking Brake	Foot-Operated Parking Brake
Heavy Duty Sealed Transaxle	Heavy-Duty Direct Drive Helical Gear with 12.44:1 Ratio