



PACK MULE

RELIABLE PRODUCTS AND SERVICE



SCT-7750-IB



SCT-7750-IB STANDARD FEATURES

- Industry Leading 3 Year Warranty
- Dual Front Wheels
- Programmable Performance Characteristics (Maximum Speed, Acceleration Rate, etc.)
- Precision Track, Direct Gear Steering
- Sealed Direct Drive Transaxle
- Heavy Duty Horn
- 6 Ply Load Range C Tires
- Rubber Deck Cover
- Universal Hitch Plate
- Adjustable Backrest

- Maintenance Management System
- Dashboard Smart Gauge (L.E.D. Battery Status, Hour Meter & Diagnostic Codes)
- State-of-the Art, Fully Sealed, Tamper Proof & Programmable Controller with On-Board Diagnostics
- Programmable Regenerative Braking
- Extra Heavy-Duty Steel Construction (14 Gauge Genuine Diamond Plate Exterior)
- Electronic Throttle
- Contactor-less Drive System
- Ergonomic Comfort Matting

SC-7750-IB

NOTE: To Provide the Flexibility to Adapt to the User's Requirements, the SCT 7750-IB Is Offered Without Battery or Charger (Although Optional Battery & Charger Are Available as Described Below*)

STOCK CHASER - BURDEN CARRIER - TOW TRACTOR - MAINTENANCE VEHICLE - PERSONNEL CARRIER

OPTIONAL EQUIPMENT
24 V 325 AH Industrial Battery*
Two Types of Chargers*: (1) High Frequency "Opportunity Charge" Capable Charger, and (2) Standard, Ferro Resonant Transformer Charger
AC Drive System
Roll Out Battery Exchange System
Carts with Chargers for Roll Out Batteries
Solid Rubber Tires
Solid Non-Marking Rubber Tires
Cushion Solid Rubber Tires
Left Foot Operator's Presence Switch
Back-Up Alarm
Proximity Alarm
Flashing Safety Beacon
Head Light, Tail Light
Hand Lever Parking Brake
Galvanized & Stainless Steel Decks
Galvanized Frame
Protective Front Guard with Rubber Bumpers
Extended Deck Lengths
5 or 6 Step Ladder (87 in. or 95 in.)
Deck Shelves
Stake Bed/Rails
Custom Cargo Restraints
Modular Work Station
Mounted Clipboards (Large & Small)
Variety of Hitches
Perma-Key Switch
Programmable Key Switch
12 Volt Power Supply for Electronic Devices
Diagnostic Handset

DIMENSIONS	
Length	78 in. (198.1 cm)
Width	32 in. (81.3 cm)
Height	50 in. (127 cm)
Wheel Base	40 in (101.6 cm)
Ground Clearance	3 in. (7.6 cm)
Deck Height	24 in. (61 cm)
Deck	Front: 31.5 in. (80 cm) x 48 (121.9 cm)
Turning Radius	55 in. (139.7 cm)
CAPACITIES	
Maximum Personnel	1
Deck	1000 lbs. (544.3 kg)
Towing	5000 lbs. (2268 kg)
WHEELS & TIRES	
Wheels	4
Tires	Pneumatic 4.80 x 8 LRC (6 Ply)
ELECTRICAL	
Battery Compartment	Battery Compartment is 31.85" L x 15.1" W x 14.6" H to Accommodate Optional 24 v. Industrial Battery
System Voltage	24 v.
Sealed Motor (Separately Excited)	5 hp (24 v.)
Sealed Programmable Controller	300 Amp (24v.)
Charger	Charger Optional to Fit Battery Selected & Preferred Charging Method
Key Switch	Removable Key
Horn	Push Button on Console
STEERING, BRAKES & TRANSAXLE	
Steering	3-Spoke Contour Wheel
Service Brakes	Self- Adjusting Wheel Drum Brakes
Electronic Brakes	Programmable Electronic Regenerative Braking
Parking Brake	Automatic Parking Brake
Heavy Duty Sealed Transaxle	Heavy-Duty Direct Drive Helical Gear with 16.99:1 Ratio

