



PACK MULE

RELIABLE PRODUCTS AND SERVICE



SCT-7750



SCT-7750 STANDARD FEATURES

Industry Leading 3 Year Warranty

Dual Front Wheels

Programmable Performance Characteristics
(Maximum Speed, Acceleration Rate, etc.)

Heavy Duty 245 Amp/Hour Batteries

Premium On-Board High Frequency Charger
with temperature compensation & automatic
cell equalization to extend the life of the
batteries

Precision Track, Direct Gear Steering

Sealed Heavy Duty Direct Drive Transaxle

Heavy Duty Horn

6 Ply Load Range C Tires

Rubber Deck Cover

Maintenance Management System

Dashboard Smart Gauge (L.E.D. Battery
Status, Hour Meter & Diagnostic Codes)

State-of-the Art, Fully Sealed, Tamper Proof
& Programmable Controller with On-Board
Diagnostics

Programmable Regenerative Braking

Extra Heavy-Duty Steel Construction (10
Gauge Uni-Body Internal Frame & 14 Gauge
Genuine Diamond Plate Exterior)

Electronic Throttle

Contactor-less Drive System

Universal Hitch Plate

Ergonomic Comfort Matting

SCT-7750

STOCK CHASER - BURDEN CARRIER - TOW TRACTOR - MAINTENANCE VEHICLE - PERSONNEL CARRIER

OPTIONAL EQUIPMENT
Upgrade to Maintenance Free AGM 250 Amp/Hour Batteries
AC Drive System
Roll Out Battery Exchange System
Carts with Chargers for Roll Out Batteries
Solid Black Rubber Tires
Solid Rubber Tires
Cushion Solid Rubber Tires
Left Foot Operator's Presence Switch
Back-Up Alarm
Proximity Alarm
Flashing Safety Beacon
Head Light, Tail Light, Brake Light
Hand Lever Parking Brake
Galvanized & Stainless Steel Decks
Galvanized Frame
Protective Front Guard with Rubber Bumpers
Extended Deck Lengths
5 or 6 Step Ladder (87 in. or 95 in.)
Deck Shelves
Stake Bed/Rails
Custom Cargo Restraints
Modular Work Station
Mounted Clipboards (Large & Small)
Variety of Hitches
Perma-Key Switch
Programmable Key Switch
12 Volt Power Supply for Electronic Devices
Diagnostic Handset

DIMENSIONS	
Length	78 in. (198.1 cm)
Width	32 in. (81.3 cm)
Height	50 in. (127 cm)
Wheel Base	40 in (101.6 cm)
Ground Clearance	3 in. (7.6 cm)
Deck Height	24 in. (61 cm)
Deck	Front: 31.5 in. (80 cm) x 48 (121.9 cm)
Turning Radius	55 in. (139.7 cm)
CAPACITIES	
Maximum Personnel	1
Deck	1200 lbs. (544.3 kg)
Towing	5000 lbs. (2268 kg)
WHEELS & TIRES	
Wheels	4
Tires	Pneumatic 4.80 x 8 LRC (6 Ply)
ELECTRICAL	
Batteries	245 Amp-Hr Lead Acid, Commercial
System Voltage (Battery Quantity)	36 v. (6-6 v.), 48 v. (8-6 v.)
Sealed Motor (Separately Excited)	7.5 hp (36 v.), 10 hp (48 v.)
Sealed Programmable Controller	300 Amp (24v. & 36 v.), 400 Amp (48 v.)
On-Board High Frequency Charger	21 Amp (36 v.), 18 Amp (48 v.)
Key Switch	Removable Safety Key Switch
Horn	Push Button on Console
STEERING, BRAKES & TRANSAXLE	
Steering	3-Spoke Contour Wheel
Service Brakes	Self- Adjusting Wheel Drum Brakes
Electronic Brakes	Programmable Electronic Regenerative Braking
Parking Brake	Automatic Parking Brake
Heavy Duty Sealed Transaxle	Heavy-Duty Direct Drive Helical Gear with 16.99:1 Ratio