



PACK MULE

RELIABLE PRODUCTS AND SERVICE



NEED TO MOVE MATERIALS MORE EFFICIENTLY?

PACK MULE BURDEN CARRIERS ARE DESIGNED TO DELIVER MAXIMUM PRODUCTIVITY
IN MISSION CRITICAL INDUSTRIAL APPLICATIONS

PACK MULE BURDEN CARRIER PORTFOLIO - OPERATOR SITTING

CAPACITIES	MEDIUM DUTY: 700/1,000 LBS. DECK & 2,000 LBS. TOWING CAPACITY			HEAVY DUTY: 1,200/1,500 LBS. DECK & 5,000/8,000 LBS TOWING CAPACITY		
IMAGE						
MODEL	BC 500	BC 520	BC 600/620	BCT 5200	BCT 6000/6200	BCG 6200
FRONT DECK	28.5" x 18"	35.5" x 18"	35.5" x 18"	35.5" x 18"	35.5" x 18"	35.5" x 21.3"
REAR DECK	28.5" x 30"	35.5" x 30"	35.5" x 48"	35.5" x 30"	35.5" x 48"	35.5" x 25"
WIDTH	29"	36"	36"	36"	36"	36"
LENGTH	78"	78"	105"	78"	105"	85"
WHEEL BASE	67"	67"	71"	67"	71"	60.7"
TURNING RADIUS	74.5"	74.5"	92"	74.5"	92"	80"
DECK HEIGHT	22.5"	22.5"	22.5"	22.5"	22.5"	25.5"
DECK LOAD	1,000 LBS.	1,000 LBS.	1,000 LBS.	1,200 LBS.	1,200 LBS.	1,200 LBS.
TOW LOAD	2,000 LBS.	2,000 LBS.	2,000 LBS.	5,000 LBS.	5,000 LBS.	8,000 LBS.

STANDARD FEATURES ON ALL PACK MULE BURDEN CARRIERS

Dual Front Wheels
 Programmable Performance Characteristics (Maximum Speed, Acceleration Rate, etc.)
 Sealed Direct Drive Transaxle
 Extra Heavy-Duty Steel Construction (10 Gauge Uni-Body Internal Frame & 14 Gauge Genuine Diamond Plate Exterior)
 Contactor-less Drive System
 Maintenance Management System

Heavy Duty 245 Amp/Hour Batteries
 Premium On-Board High Frequency Charger with temperature compensation & automatic cell equalization to extend the life of the batteries
 Programmable Regenerative Braking
 Dashboard Smart Gauge (L.E.D. Battery Status, Hour Meter & Diagnostic Codes)
 6 Ply Load Range C Tires
 Universal Hitch Plate

Ask Us for an “Apples to Apples” Feature and Price Comparison to Any Other Products in the Market!



Ask Us How You Can Try Before You Buy!



Pack Mule Burden Carriers Offer Outstanding Maneuverability Along with Programmable Performance Characteristics to Accommodate the Specific Requirements of the User's Individual Environment and Application!

PACK MULE BURDEN CARRIER PORTFOLIO - OPERATOR STANDING

CAPACITIES	MEDIUM DUTY: 1,000 LBS. DECK & 2,000 LBS. TOWING CAPACITY			HEAVY DUTY: 1,200/1,500 LBS. DECK & 5,000/8,000 LBS TOWING CAPACITY		
IMAGE						
MODEL	BC 625	SC 750	SC 775	BCT 6250	SCT 7750	SCT 7750-IB
FRONT DECK	35.5" x 18"	28.5" x 48"	31.5" x 48"	35.5" x 18"	31.5" x 48"	31.5" x 48"
REAR DECK	35.5" x 53"	N/A	N/A	35.5" x 53"	N/A	N/A
WIDTH	36"	29"	32"	36"	32"	32"
LENGTH	93"	78"	78"	93"	78"	78"
WHEEL BASE	60"	40"	40"	60"	40"	40"
TURNING RADIUS	80"	55"	55"	80"	55"	55"
DECK HEIGHT	22.5"	24"	24"	22.5"	24"	24"
MAXIMUM PERSONNEL	1 Standing	1 Standing	1 Standing	1 Standing	1 Standing	1 Standing
DECK LOAD	1,000 LBS.	1,000 LBS.	1,000 LBS.	1,200 LBS.	1,200 LBS.	1,000 LBS.
TOW LOAD	2,000 LBS.	2,000 LBS.	2,000 LBS.	5,000 LBS.	5,000 LBS.	5,000 LBS.

OPTIONAL EQUIPMENT FOR ALL PACK MULE BURDEN CARRIERS

- AC Drive System
- Roll Out Battery Exchange System
- Tire Upgrades to Solid Black, Solid Non-Marking & Soft Solid
- Back-Up & Proximity Alarms
- Extended Deck Lengths, Deck Shelves, Stake Bed/Rails & Cargo Restraints
- Left Foot Operator's Presence Switch
- 12 Volt Power Supply for Electronic Devices

- Upgrade to Maintenance Free AGM 250 Amp/Hour Batteries
- Protective Front Guard with Rubber Bumpers
- Head Light & Tail Light
- Flashing Safety Beacon
- 5 or 6 Step Ladder (87 in. or 95 in.)
- Variety of Hitches
- Perma-Key and Programmable Key Switches